

LinxTower



Mass CD and DVD duplication

Expands from 10 up to 2550 target drives

Ideal for live events

Easy to use

The Linx Tower duplication system is a revolutionary solution that will expand to allow you to link up to 255 ten drive towers to give an incredible 2550 simultaneous target drives.

Each ten target drive tower is linked to another via a D-sub 15 connection. Once you put a master disc into one of the towers and press copy the data will pass to the next tower through the high performance daisy chain cables.

Alternatively duplication can be made from a master stored on the 160GB hard drive for even faster duplication times. Whether you're a novice or a duplication expert, you'll find Linx Tower to be a great tool, due to its speed, accuracy and reliability Linx Tower duplicators can also be used as stand alone CD/DVD 10 target towers as well as being linked together to form chains of duplicators. Linx Tower supports up to 48x CD duplication or 16x DVD duplication, depending on the model chosen. A USB 2.0 connection provides you with the option to link to your PC and make one of the CD/DVDRW drives inside your duplicator tower as an external optical drive.

Designed to withstand 24/7 operation and heavy production runs the Linx Tower Duplicators enhanced vented air circulation system means that your towers never require cooling off periods.

Rigorously tested for performance and reliability, Linx Towers are manufactured to strict quality control standards with an aluminium case and built in power supplies, delivering enhanced duplication at every level and at all times.

LinxTower

Function: CD/DVD Copier

Media Handling: DVD±R/RW, DVD+R DL, DVD-ROM, DVD-Video, CD-R/RW, Audio CD, CD-ROM, CD-DA, CD-ROM XA, Multi-Session Photo CD, CD-I, D Extra, VCD, CD+G

Targets: 10 targets per tower, up to total of 2550 targets

Drives: CD-R or DVD±R

Maximum Writing Speeds: 16x DVD±R/48xCD-R

Link Type: D-sub 15

Interface/Connectivity: IDE
USB 2.0

Internal Hard Drive 160GB Standard

Dimensions (WxHxD): 7.5" x 25" x 16.25"
190mm x 635mm x 417mm

Weight: Approx. 55lbs (25kg)

Voltage: Input: 100~240V AC
Output: +5V DC, 3.8A

Operating Temperature: 30°F ~ 100°F

Operating Humidity: 10% ~ 80%

Regulations: FCC, CE, RoHS

Operation: No PC Required



Throughput

No. Drives	10	20	50	100
700MB CD:	200	400	1000	2000
4.7GB DVD:	100	200	500	1000

Warranty

12 months back to base, all parts and labour included.
2nd year excludes drives, hard drives and carriage.
Extended warranties also available.



Verity Systems maintains a policy of continuous improvement and reserves the right to amend this specification without notice.

web: www.veritysystems.com

email: sales@veritysystems.com

tel: +44 (0) 1252 317000

fax: +44 (0) 1252 316555